

## DECLARATION OF PERFORMANCE N°

**F35086150719**

1. Unique identification code of the product-type

**RENOLIT ALKORTOP F 35086**

2. Intended use

Plastic sheets for roof waterproofing  
Exposed sheets - Mechanically fastened

3. Manufacturer

Renolit Belgium NV  
Industriepark De Bruwaan 43  
9700 Oudenaarde - Belgium

4. Authorised representative

-

5. System of AVCP

System 2+

6a. Harmonised standard

EN 13956 : 2012

Notified Body

MFPA N° 0800

6b. European Assessment Document

-

Notified Body

7. Declared performances

External fire performance (EN 13501-1, CEN/TS 1187)

Froof

Reaction to fire (EN 13501-1, EN ISO 11925-2)

E

Watertightness (EN 1928/B)

Pass

Tensile strengthforce (EN 12311-2/A)

MLV >= 1200 N/50 mm

Elongation (EN 12311-2/A)

MLV >= 19 %

Resistance to root penetration (EN 13948)

NPD

Resistance to static load (EN 12730/B and C)

MLV >= 20 kg

Resistance to impact (EN 12691/A)

MLV >= 700 mm

Resistance to impact (EN 12691/B)

MLV >= 950 mm

Tear resistance (EN 12310-2)

MLV >= 320 N

Joint peel resistance (EN 12316-2)

MLV >= BOJ or 300 N/50 mm

Joint shear resistance (EN 12317-2)

MLV >= BOJ or 500 N/50 mm

Artificial ageing (EN 1297)

Grade 0

Foldability at low temperature (EN 495-5)

MLV <= - 30 °C

Dangerous substances

Conform \*

\* This product is an article as identified in article 3 of Regulation (EU) N° 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (Substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

8. Appropriate Technical Documentation

Manufacturer instuctions

The performance of the product identified above is in conformity with the set of declared performances. This declarartion of performance is issued, in accordance with Regulation (EU) N° 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
Oudenaarde

Dirk Van der Sype  
20/04/2023



Rely on it.

A handwritten signature in blue ink, appearing to read 'Dirk Van der Sype', with a long horizontal stroke extending to the right.

**DECLARATION OF PERFORMANCE N°****F35086180719**

1. Unique identification code of the product-type

**RENOLIT ALKORTOP F 35086**

2. Intended use

Plastic sheets for roof waterproofing  
Exposed sheets - Mechanically fastened

3. Manufacturer

Renolit Belgium NV  
Industriepark De Bruwaan 43  
9700 Oudenaarde - Belgium

4. Authorised representative

-

5. System of AVCP

System 2+

6a. Harmonised standard

EN 13956 : 2012

Notified Body

MFPA N° 0800

6b. European Assessment Document

-

Notified Body

7. Declared performances

External fire performance (EN 13501-5, CEN/TS 1187)

Froof

Reaction to fire (EN 13501-1, EN ISO 11925-2)

E

Watertightness (EN 1928/B)

Pass

Tensile strength (EN 12311-2/A)

MLV &gt;= 1200 N/50 mm

Elongation (EN 12311-2/A)

MLV &gt;= 19 %

Resistance to root penetration (EN 13948)

NPD

Resistance to static load (EN 12730/B and C)

MLV &gt;= 20 kg

Resistance to impact (EN 12691/A)

MLV &gt;= 900 mm

Resistance to impact (EN 12691/B)

MLV &gt;= 1300 mm

Tear resistance (EN 12310-2)

MLV &gt;= 320 N

Joint peel resistance (EN 12316-2)

MLV &gt;= BOJ or 300 N/50 mm

Joint shear resistance (EN 12317-2)

MLV &gt;= BOJ or 500 N/50 mm

Artificial ageing (EN 1297)

Grade 0

Foldability at low temperature (EN 495-5)

MLV &lt;= - 30 °C

Dangerous substances

Conform \*

\* This product is an article as identified in article 3 of Regulation (EU) N° 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (Substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

8. Appropriate Technical Documentation

Manufacturer instructions

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) N° 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
OudenaardeDirk Van der Sype  
20/04/2023

Rely on it.

A handwritten signature in blue ink, appearing to be 'Dirk Van der Sype'.

## DECLARATION OF PERFORMANCE N°

**F35086200719**

1. Unique identification code of the product-type

**RENOLIT ALKORTOP F 35086**

2. Intended use

Plastic sheets for roof waterproofing  
Exposed sheets - Mechanically fastened

3. Manufacturer

Renolit Belgium NV  
Industriepark De Bruwaan 43  
9700 Oudenaarde - Belgium

4. Authorised representative

-

5. System of AVCP

System 2+

6a. Harmonised standard

EN 13956 : 2012

Notified Body

MFPA N° 0800

6b. European Assessment Document

-

Notified Body

7. Declared performances

External fire performance (EN 13501-5, CEN/TS 1187)

Froof

Reaction to fire (EN 13501-1, EN ISO 11925-2)

E

Watertightness (EN 1928/B)

Pass

Tensile strength (EN 12311-2/A)

MLV >= 1200 N/50 mm

Elongation (EN 12311-2/A)

MLV >= 19 %

Resistance to root penetration (EN 13948)

NPD

Resistance to static load (EN 12730/B and C)

MLV >= 20 kg

Resistance to impact (EN 12691/A)

MLV >= 900 mm

Resistance to impact (EN 12691/B)

MLV >= 1300 mm

Tear resistance (EN 12310-2)

MLV >= 320 N

Joint peel resistance (EN 12316-2)

MLV >= BOJ or 300 N/50 mm

Joint shear resistance (EN 12317-2)

MLV >= BOJ or 500 N/50 mm

Artificial ageing (EN 1297)

Grade 0

Foldability at low temperature (EN 495-5)

MLV <= - 30 °C

Dangerous substances

Conform \*

\* This product is an article as identified in article 3 of Regulation (EU) N° 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (Substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

8. Appropriate Technical Documentation

Manufacturer instructions

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) N° 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
Oudenaarde

Dirk Van der Sype  
20/04/2023



Rely on it.

A handwritten signature in blue ink, appearing to read 'Dirk Van der Sype', written over a horizontal line.